

### Doublestream trimmer RS234

|                                   |                |
|-----------------------------------|----------------|
| Manufacturer                      | Gämmerler GmbH |
| Type                              | RS234          |
| Serial number/year of manufacture | 2018           |

### Performance

|                          |  |
|--------------------------|--|
| Power                    | 80 (optional 100) m/min.                             |
| Pagination <sup>1</sup>  | 4 – 96   |
| Format untrimmed         | min. 122 x 122 mm<br>max. 530 x 530 mm               |
| Format trimmed           |  |
| 2-edge trim              | min. 118 x 118 mm<br>max. 526 x 526 mm               |
| 1-edge trim              | min. 115 mm  |
| Trim width <sup>2</sup>  | min. 2 mm - max. 65 mm                               |
| Trim-Depth <sup>3</sup>  | max. 13 mm   |
| Trimming system          | shingle or single trim                               |
| Type of printed products | gravur and offset-printing (heatset and non-heatset) |

### Main drive

|                        |                         |
|------------------------|-------------------------|
| Three-phase gear motor | 2 x 1,5 kW - 1500U/min. |
|------------------------|-------------------------|

### Knife drive

|                         |                         |
|-------------------------|-------------------------|
| Three-phase brake motor | 2 x 3,0 kW – 3000U/min. |
|-------------------------|-------------------------|

The sound pressure level does not exceed 80 dB (A) corresponding to EN 13 023.

### Physical

|   |                       |
|---|-----------------------|
| Outer dimensions<br>(Lenght x Width x Height) | 1770 x 1520 x 2005 mm |
|---|-----------------------|

<sup>1</sup> depending on page property (Gram weight, pagination)

<sup>2</sup> depending on page property (Gram weight, pagination)

<sup>3</sup> depending on page property (Gram weight, pagination)

### Air consumption

|                         |                   |
|-------------------------|-------------------|
| Nominal pressure        | 6 - 8 bar         |
| Max. operating pressure | 8 bar (0,8 MPa)   |
| Air consumption         | 2 x max. 3400 l/h |

Air pressure quality according to DIN ISO 8573-1 of quality class 3.

### Exhaustion for paper trim

|                  |                             |
|------------------|-----------------------------|
| 1 knife blocks   | 1 x Ø 100 mm                |
| 2 knife blocks   | 2 x Ø 100 mm                |
| 3 knife blocks   | 3 x Ø 100 mm                |
| 4 knife blocks   | 4 x Ø 100 mm                |
| Exhaustion speed | 28 – 30 m/s (92 – 100 ft/s) |
| Vakuum           | 1500 Pa (N/m <sup>2</sup> ) |

### Electrical loads

|                 |            |
|-----------------|------------|
| Power           | 2 x 7,5 kW |
| Supply Voltage  | 380 V      |
| Nominal current | 12 A       |
| Full load Amps. | 2 x 25 A   |
| Frequency       | 50 (60) Hz |
| Control voltage | 24 V       |

### Status

As new with warranty

### Pictures

following

### Price

On demand